

# Beneath the Surface

## CARPET TILE SPECIFICATIONS

CONSTRUCTION
PILE FIBER
TUFTING GAUGE
PILE HEIGHT
TOTAL CARPET WEIGHT
BACKING STRUCTURE
PILE TREATMENT
TILE SIZE

## ECOSQUARE BACKING

Multi Level Texture Tufted
100% Solution Dyed Nylon
1/12 inch
3.0 - 5.5 mm.
4,111 gram/sq.m.
 <b>EcoSquare®</b> Reinforced Recycled Backing
Stain and Soil Protection
25 x 100 cm.

## ECOSOFT BACKING

Multi Level Texture Tufted
100% Solution Dyed Nylon
1/12 inch
3.0 - 5.5 mm.
2,996 gram/sq.m.
 <b>EcoSoft®</b> Recycled Cushion Backing
Stain and Soil Protection
25 x 100 cm.

## PERFORMANCE

END USE CLASSIFICATION
CASTER CHAIR INDEX
DIMENSIONAL STABILITY
ELECTROSTATIC PROPENSITY
COLORFASTNESS TO LIGHT
INDOOR AIR QUALITY

BS EN 1307 Class 33 – Heavy Commercial
BS EN 985 ≥ 2.4
BS EN 986 < 0.15%
AATCC 134 < 3 KV
ISO 105 B02 Min L6
GLP 1022

BS EN 1307 Class 33 – Heavy Commercial
BS EN 985 ≥ 2.4
BS EN 986 < 0.15%
AATCC 134 < 3 KV
ISO 105 B02 Min L6
GLP 7543

## FLAMMABILITY

HOT METAL NUT
RADIANT PANEL TEST
SMOKE DENSITY
SURFACE FLAMMABILITY
FIRE CLASSIFICATION

BS 4790 Low Radius
ASTM E648 Class 1
ASTM E662 < 450
ASTM D 2859 Passes
-

BS 4790 Low Radius
ASTM E648 Class 1
ASTM E662 < 450
ASTM D 2859 Passes
BS EN 13501 Class B <sub>1</sub> -s <sub>1</sub>

## ACOUSTIC BEHAVIOUR

SOUND ABSORPTION
------------------

BS EN ISO 354 NRC 0.15 or higher
----------------------------------


BS EN ISO 354 NRC 0.30 or higher (Superior Noise Reduction)
--

## CERTIFICATION




## INSTALLATION METHOD

25 x 100 cm.



Random Vertical Brick



Herringbone

Specifications are subject to normal manufacturing tolerances, and subject to change without prior notice.  
 As in all quality carpets, colors are subject to dye lot variations.

## Headquarters

2054 New Petchburi Road  
 Bangkapi, Huaykwang, Bangkok 10310 Thailand  
 Tel +66 (0) 2314-5402, Fax +66 (0) 2318-3537  
 www.carpetsinter.com, info@carpetsinter.com

