

MACHINE TUFTED CARPET TILE
PERFORMANCE AND SPECIFICATION

Specification

Collection	: URBAN ELEMENT - PENTHOUSE PLUS
Construction	: Tufted Level Loop
Yarn Content	: 100% Solution Dyed Polypropylene
Machine Gauge	: 1/10 inch
Pile Height	: 4.0 mm 0.157 inch
Pile Weight	: 644 gm/sm 19.0 oz/sy
Total Weight	: 3930 gm/sm 115.9 oz/sy
Primary Backing	: Non Woven Polyester Spunbonded
Secondary Backing	: EcoSquare® Reinforced Recycled Backing
Tile Size	: 50 x 50 cm.

Performance Test and Treatment


Surface Flammability	ASTM D2859 / CPSC FF 1-70 Pill Test Pass
Flammability - Hot Metal Nut	BS 4790 Low Radius
Electrostatic Propensity	AATCC 134 Permanent Anti-Stat ≤ 3.0 KV
Overall Classification	BS EN 1307 General
Dimensional Stability	BS EN 986 ≤ 0.15%
Colourfastness to Light	ISO 105 B02 Minimum 6

LEED Credit Contribution

Material & Resources:

Building Product Disclosure and Optimization - Sourcing of Raw Materials	Option 2: Recycled Content
Building Product Disclosure and Optimization - Material Ingredients	Option 1: Health Product Declaration Option 2: Contains No Ingredients Listed On The REACH Authorization or Candidate List

Installation Method



Visibility of Carpet Tile Seams in Solid or Near-Solid Color Tiles - Disclaimer

It is expected that the seams of solid and near-solid carpet tiles will be visible. This is not considered or accepted as a product defect because it is due to the inherent characteristic of a distinct object (the tile in this case) in a solid color. It is what you see in any flooring material that is modular such as wood planks and ceramic tiles.

For Solid or Near-Solid color tiles, we recommend a quarter-turn installation for square tiles and a herringbone installation for plank tiles. These installed configurations create a subtle texture on the floor by utilizing the visibility of the seams.

If you prefer a carpet tile that masks most seams, select a product that has a multicolor pattern or texture that can minimize the visibility of tile seams in most applications. Please consult with your Carpets Inter rep for further guidance.

Certification and Standards



We apply strict quality control at all stages of production, in compliance with ISO 9001. However, the carpet manufacturing process is a complex series of operations and variations in the specifications could occur. This will not have any detrimental effect on the performance of the product. We reserve the right to amend this specification without prior notice.