# **Breathe**

Inhale & Exhale

## CARPET TILE SPECIFICATIONS

CONSTRUCTION		
PILE FIBER		
TUFTING GAUGE		
PILE HEIGHT		
TOTAL CARPET WEIGHT		
BACKING STRUCTURE		
PILE TREATMENT		
STANDARD MODULE SIZE		
PERFORMANCE		

	END USE CLASSIFICATION
	CASTER CHAIR INDEX
	DIMENSIONAL STABILITY
	ELECTROSTATIC PROPENSITY
	COLORFASTNESS TO LIGHT
	INDOOR AIR QUALITY
П	AMMADILITY

### FLAMMABILITY

HOT METAL NUT	
RADIANT PANEL TEST	
SMOKE DENSITY	
SURFACE FLAMMABILITY	
SOUND ABSORPTION	

# NOISE REDUCTION COEFFICIENT

# **EcoSquare**®

Multi-Level Loop Texture 100% Solution Dyed Nylon 1/12 inch 3.0 - 5.5 mm. 4,115 gram/sq.m.

# EcoSquare\* Reinforced Recycled Hard Back

Stain and Soil Protection Inhale 50x50 cm., Exhale 25x100 cm.

BS EN 1307 Class 33 - Heavy Commercial BS EN 985 ≥ 2.4 BS EN 986 < 0.15% AATCC 134 < 3 KV ISO 105 B02 Min L6 GLP 1022

BS 4790 Low Radius ASTM E648 Class 1 ASTM E662 < 450 ASTM D 2859 Passes

BS EN ISO 354 NRC 0.15 or higher

# **EcoSoft®**

Multi-Level Loop Texture 100% Solution Dyed Nylon 1/12 inch 3.0 - 5.5 mm. 3,000 gram/sq.m.

EcoSoft\*
Recycled PET Cushion Back Stain and Soil Protection

Inhale 50x50 cm., Exhale 25x100 cm.

BS EN 1307 Class 33 - Heavy Commercial BS EN 985 ≥ 2.4 BS EN 986 < 0.15% AATOC 134 < 3 KV ISO 105 B02 Min L6 GLP 7543

BS 4790 Low Radius ASTM F648 Class 1 ASTM E662 < 450 ASTM D 2859 Passes

BS EN ISO 354 NRC 0.30 or higher



# **CERTIFICATION**















Specifications are subject to normal manufacturing tolerances, and subject to change without prior notice. As in all quality carpets, colors are subject to dye lot variations.

### **INSTALLATION METHOD**

### Inhale



Monolithic Checkerboard




Horizontal Brick



Monolithic 1/4 Step

### Exhale



Random Vertical Brick



# Headquarters

